



# INTRODUCING THE SELIM HINGE

## Key Features

- **Robust Strength:** Built from high-strength alloy, capable of supporting doors up to 100kg (with 3 hinges).
- **Quick Installation:** Integrated wing locator for precise and efficient fitting.
- **Smooth and Quiet Operation:** Flanged nylon bushes and stainless-steel hinge pins for enhanced longevity and performance.
- **Corrosion Resistance:** 6mm stainless-steel pins with machined chamfered ends for durability.
- **Secure Assembly:** Aluminium fitted endcaps for performance and durability.
- **Versatile Use:** Suitable for aluminium entrance doors and timber door applications.
- **Minimum Door Thickness:** 40mm.
- **Door Closer Compatibility:** Use at least 3 hinges when installing with a door closer



## High-Performance Hinges for Aluminium & Timber Doors Strength and Efficiency Combined.

The SELIM hinge is designed to withstand the high demands of commercial and heavy-use environments. Made from top-quality materials and optimised for quick installation, it ensures exceptional durability and performance for both aluminium and timber doors.



Scan here to view our full range of architectural hardware

## Available Selim Hinge Options

Code	Finish
520SCH130INF	Satin Chrome
520PBH130INF	Matt Black

For all enquiries:  
**T:** 0800 663 5766 | **E:** info@milesnelson.co.nz

